



Ericsson /MediaKind AVP4000 Chassis (Dual PSU) with 1 x EI9001 & 1 x Ce-A Encoder cards

S/N: FL54469

Model	Build Version:	Serial:
Advanced Video Processor	9.42.9.Build1	FL54469

S Number	Description	Serial Number	HW	
Base Unit	S15980	Host Plus Controller Card	27411	10.0
Slot 1	S15860	EI9001 VCM	18781	7.1
Slot 2	S14945	CE-a Pre-Processor	9431	4.3
Slot 3	empty			
Slot 4	empty			
Slot 5	empty			
Slot 6	empty			

**Host**

Chip ID:71 A3 28 7D 2C 0B

License	Status	In Use	Available	Description	Expires	Time Left
AVP/SWO/422/10-BIT	enabled	100	100	Allows 10 bit encoding in HD H264 4:2:2 mode		
AVP/SWO/DOLBY/AC3	enabled	100	100	Allows one channel (stereo pair) of audio to be encoded using the Dolby Digital format. Three licences are required for 5.1 encoding.		
AVP/SWO/DOLBY/PLUS	enabled	100	100	Allows a channel pair of audio to be encoded using the Dolby Digital Plus format.		
AVP/SWO/DOLBY E/DEC	enabled	100	100	Allows for the decode of one Dolby E bitstream consisting of up to 8 channels in transcode.		
AVP/SWO/DOLBY/AC3/DEC	enabled	100	100	Allows for the decoding of one Dolby Digital bitstream consisting of up to 5.1 channels in transcode.		
AVP/SWO/M1L2	enabled	100	100	Allows one stereo pair of audio to be encoded using the MPEG-1 Layer II format		
VP/SWO/SDMP2/420	enabled	100	100	Allows the module to code MPEG-2 SD video.		
VP/SWO/SDMP2/NR	enabled	100	100	This feature will allow temporal and spatial filtering techniques to reduce the presence of noise in the picture before it is encoded		
AVP/SWO/MCTF	enabled	100	100	This feature will allow temporal and spatial filtering techniques to reduce the presence of noise in the picture before it is encoded		
AVP/SWO/REFLEX	enabled	100	100	This will allow the module to be part of a statmux pool of encoders that share their bit rate using an external multiplexer		
AVP/SWO/PROFEC	enabled	100	100	This enables the Pro MPEG FEC feature on the IP output.		
AVP/SWO/AAC	enabled	100	100	Allows one channel (stereo pair) of audio to be encoded using the AAC/HE-AAC format.		
VP/SWO/SD/MCTF	enabled	100	100	This feature will allow temporal and spatial filtering techniques to reduce the presence of noise in the SD picture before it is encoded		
AVP/SWO/DPI	enabled	100	100	This enables the video splicing feature.		
AVP/SWO/PAA	enabled	100	100	This feature enables phase aligned MPEG-2 Layer II audio encode.		
AVP/SWO/PIP	enabled	100	100	This enables one PiP Channel.		
AVP/SWO/ALC	enabled	100	100	Enables one stereo pair of Automatic Loudness Control (VP/SWO/ALC).		



AVP/SWO/PSIP	enabled	100	Enables PSIP carousel support via the RCP interface
AVP/SWO/BISS	enabled	100	This enables BISS encryption.
AVP/SWO/MP4	enabled	100	Enables one H.264 Video Encoder
AVP/SWO/HD	enabled	100	Enables one HD Video Encoder
AVP/SWO/MP2	enabled	100	Enables one MPEG-2 Video Encoder
AVP/SWO/REMUX	enabled	100	This enables the addition of externally generated transport stream data to a transport stream
AVP/SWO/TRANS	enabled	100	Enables one EI9000 to perform transcoding
AVP/SWO/API	enabled	100	Enables the REST API
AVP/SWO/1080P	enabled	100	Enable one channel of 1080P coding for 3G input
AVP/SWO/CAPPEDVBR	enabled	100	Enable the Capped VBR Buffer mode for EI9000 and EI9000T cards
AVP/SWO/SD/PREMIUM	enabled	100	Enable Premium SD picture video quality for EI9000 and EI9000T cards
AVP/SWO/HD/PREMIUM	enabled	100	Enable Premium HD picture video quality for EI9000 and EI9000T cards
AVP/SWO/ABR/SD	enabled	100	Enables SD Adaptive Streaming output on one card
AVP/SWO/ABR/HD	enabled	100	Enables HD Adaptive Streaming output on one card
AVP/SWO/422/DEC	enabled	100	Allows decoding AVC 4:2:2 10-bit

Slot 2: CE-a

Chip ID:37 39 33 20 D7 24

License	Status	In Use	Available Description	Expires Time Left
CE/SWO/CE-x/H264	enabled	100	This feature enables SD H.264 encoding (main channel).	
CE/SWO/CE-x/HD	enabled	100	This feature enables HD encoding.	
CE/SWO/CE-x/422	enabled	100	This feature enables 4:2:2 and 10 bit encoding of MPEG-2 and H.264 (if the H.264 license is available).	
CE/SWO/3D	enabled	100	This enables 3D operation.	
CE/SWO/MCTF	enabled	100	This feature will allow temporal and spatial filtering techniques to reduce the presence of noise in the picture (SD or HD) before it is encoded	
CE/SWO/DPI	enabled	100	This enables the video splicing feature.	
CE/SWO/M1L2	enabled	100	Allows one stereo pair of audio to be encoded using the MPEG-1 Layer II format	
CE/SWO/AAC	enabled	100	Allows one channel (stereo pair) of audio to be encoded using the AAC/HE-AAC format.	
CE/SWO/DOLBY/AC3	enabled	100	Allows one channel (stereo pair) of audio to be encoded using the Dolby Digital format	
CE/SWO/PAA	enabled	100	This feature enables phase aligned MPEG-2 Layer II audio encode.	
CE/SWO/CE-a/H264	enabled	100	This feature enables SD H.264 encoding.	
CE/SWO/CE-a/HD	enabled	100	This feature enables HD encoding.	
CE/SWO/CE-a/HDJ2K	enabled	100	This feature enables HD JPEG2000 encoding.	
CE/SWO/CE-x/1080p	enabled	100	This feature enables H264 1080p encoding.	
CE/SWO/CE-a/1080pJ2K	enabled	100	This feature enables J2K 1080p encoding.	
CE/SWO/CE-x/STRIPE	enabled	100	This feature enables H264 Stripe Refresh encoding.	